

100% ACRYLIC WATER-BASED PAINTS

# PERMAPLASTIK

INSPIRATION FOR YOUR IMAGINATION

## DESCRIPTION

Permaplastik is a 100% acrylic water based flat finish suitable for both interior and exterior use. Note however the Glow colours have limited exterior durability with respect of colour stability.

## USES

This versatile finish is suitable for use for television, film, theatrical and photographic sets, displays and exhibition fixtures, sign writing, posters and interior or exterior architectural feature decoration. Permaplastik provides a smooth, matt finish in a range of rich, vibrant colours that may be mixed to create colours of your own imagination.

## COLOURS

33 full-strength colours inclusive black + white, and iridescent METALLIC range and GLOW range. In addition a CLEAR GLOSS & CLEAR MATT 'VARNISH' is available.

## GLOSS LEVEL

Flat.

## DURABILITY

Excellent\*

\*Glow Colours have a life of approximately 3 months when used on exterior surfaces.

## SURFACE PREPARATION

**New paper-faced wallboard. Hardboard, new plaster, fibrous plaster, cement bricks:** Brush down with a stiff fibre brush to remove loose and powdery material. Fill cracks with filler, sand and dust down. Apply one coat of Permaplastik Acrylic Sealer undercoat in White or N23 Grey. Use of N23 Grey is recommended where optimum opacity is required over old contrast colours. **Stir well before use with a broad, flat paddle.**

**Previously Painted Surfaces:** Scrape loose and flaking paint off, sand smooth and dust down. On greasy or soiled surfaces wash with sugar soap, then wipe down with a clean damp rag.

## APPLICATION

Brush, Roller or Spray. Apply liberally using a fully loaded brush or roller. Generally use a 10mm nap roller cover, however in the case of rough textured surfaces use a 20mm nap roller cover.

## DRY TIME

At approximately 25°C, 20 minutes to touch dry.

## RECOAT TIME

2 hours dry to re-coat. Under cooler and/or humid conditions allow longer times.

## COVERAGE

Approximately 12-16 square metres per litre (depending upon surface type and general condition).

## CLEAN UP

Water.

## PRECAUTIONS

Always stir paint thoroughly prior to use. Use a flat, wide stirrer in a circular lifting motion for at least 5 minutes. The product is supplied ready for use but may be thinned with water only up to a maximum of 100 ml per litre. On very absorbent surfaces (e.g. set plaster), dampen the surface prior to application.

VER 1212

The information and recommendations contained in this Product Information sheet, as well as technical advice otherwise given by representatives of our Company, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and on condition that users shall make their own tests to satisfy themselves that they will fully meet their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product information sheet out of date and users are requested to ensure that they follow current recommendations