



## FEATURES AND BENEFITS

**PERMAPLASTIK** is a 100% acrylic flat water-based paint formulated especially for use in a wide range of architectural, scenic and decorative applications. **PERMAPLASTIK** is ideally suited to the decoration of television, film, theatrical and photographic sets, displays and exhibition fixtures, sign-writing, canvas banners and interior or exterior architectural feature decoration.

**Scenic Range:** Consists of 20 full-strength colours made from the finest quality pigments in an acrylic base which can be mixed with white or other colours in the scenic range. **PERMAPLASTIK** is easily applied and cleaned up in water using conventional methods, and features excellent coverage and a dead flat (non-reflective) finish which can be re-worked after one hour's drying time.

**Glow Range:** Consists of 8 fluorescent colours- best results being achieved when applied on a white background such as **PERMAPLASTIK** Scenic White or **PERMAPLASTIK** Acrylic Sealer Undercoat.

**Metallics:** Consisting of 5 metallic colours - can be used as supplied or tinted to create special effects.

**Varnishes & Primers:** Consisting of 2 clear (gloss & matt) varnishes and 2 primers (white & N23 grey)

New additions to the range include the N23 GREY PRIMER, ideal for use under the deeper GLOW colours in broad wall application. CRIMSON, RAW UMBER, and PEARL WHITE.

**PERMAPLASTIK** is available in 300ml, 1L, 4L and 15L\* sizes.

\*Only certain colours available in the 15L size

## APPLICATION GUIDE

### SURFACE PREPARATION

New paper-faced wallboard, hardboard, new plaster, fibrous plaster, cement bricks: Brush down with a stiff fibre brush to remove loose and powdery material. Fill cracks with filler, sand and dust down. Apply one coat of Permaplastik Acrylic Sealer Undercoat. Stir well before use with a broad flat paddle.

Previously painted surfaces: Scrape loose and flaking paint off, sand smooth and dust down.

On greasy or dirty surfaces wash with sugar soap.

### THINNING

Not usually required. On very absorbent surfaces (e.g. set plaster), dampen the surface and thin the first coat with up to 100mL of water per litre.

### COVERAGE

For optimum application at 10-12m<sup>2</sup> /L per coat, depending upon surface type and general condition.

### FINISHING

Apply one or two coats of Permaplastik as required. For optimum results White Permaplastik Acrylic Sealer Undercoat should be used before coating with any Permaplastik colour. For extra protection of the

**PERMAPLASTIK** flat colour can be overcoated with **PERMAPLASTIK CLEAR GLOSS** or **CLEAR MATT VARNISH**.

### DRYING TIMES

Drying times will vary depending on weather conditions at the time of application.

At approximately 25°C, 30 minutes to touch-dry; 4 hours – dry to recoat.

Under cooler or humid conditions allow longer times. Note: Do not use at temperatures below 10°C.



**CLEAN UP**

Clean equipment with mild soap and water, away from drains and open watercourses.

**SHELF LIFE**

18-24 months if stored in a cool dry place. Storage at high temperatures and high humidity may reduce self life.

**PRECAUTIONS**

Always stir paint thoroughly prior to use. Use a flat, wide stirrer in a circular lifting motion for at least 5 minutes. This product is supplied ready for use.

**VER 1406**

The information and recommendations contained in this Application sheet, as well as technical advice otherwise given by representatives of our Business, whether verbally or in writing, are based on our present knowledge and believed to be accurate. However, no guarantee regarding their accuracy is given as we cannot cover or anticipate every possible application of our products and because manufacturing methods, printing stocks and other materials vary. For the same reason our products are sold without warranty and on condition that users shall make their own tests to satisfy themselves that they will fully meet their particular requirements. Our policy of continuous product improvement might make some of the information contained in this Product information sheet out of date and users are requested to ensure that they follow current recommendations